



# SYNERGO II™

## Multi Tilt [Welding]

STANDARD	<b>BACKREST</b>	
	3" height adjustment «Floating without interval »	
	Backrest adjustment range 22" to 25"	
	Ergonomic padded backrest (20,5"w x 22,5"h)	
	Extended backrest for optimized back support	
	<b>SEAT</b>	
	High resilience velva foam	
	Streamlined seat (20"w x 17"d x 3"h)	
	<b>MULTI TILT MECHANISM</b>	
	Mechanism type «Floating without interval »	
	Floating spring tension adjustment	
	Seat height adjustment	
Seat angle adjustment		
Backrest angle adjustment		
2,5" seat depth adjustment		
<b>BASES</b>		
28" industrial steel		
<b>SEAT HEIGHT ADJUSTMENT</b>		
Cylinder 100 mm (18.5" – 22.5")		
<b>CASTERS / GLIDES</b>		
3" rubber casters (slow rolling)		

ADDITIONAL OPTIONS	Plastic back shell	
	Heavy use version	
	Extra lumbar support	
	Memory foam (seat)	
	Memory foam (backrest)	
	Height adjustable headrest (3")	
	Height adjustable headrest (3"), deep (4.5")	
	32" steel industrial base	
	24" footrest (adjustable height)	
	Tool compartment (11'w x 6'd x 1'h)	
Tool compartment (19'w x 8'd x 1'h)		

OPTIONS	<b>BACKREST</b>	
	Small ergonomic padded backrest (17,5"w x 21"h)	
	<b>ARMREST</b>	
	Standard: height and side adjustment, moves 2" forward and swivels	
	Standard: height and lateral adjustment, moves 2" forward	
	Fireproof: height, side adjustment and swivels	
	<b>SEAT</b>	
	<b>Seat size options</b>	
	Large format (24"w x 19,5"d x 5"h)	
	Long format (19,5" w x 19"d x 4"h)	
	Small format (19"w x 17"d x 3"h)	
	<b>BASES</b>	
	27" fiberglass reinforced nylon base	
	5 double nylon casters 2"	
	<b>SEAT HEIGHT ADJUSTMENT</b>	
Cylinder 80 mm (18"-21")		
Cylinder 140 mm (21"-26,5")		
Cylinder 200 mm (23"-31,5")		
Cylinder 270 mm (26,5"-36,5")		
<b>CASTERS / GLIDES</b>		
3" rubber casters with brake (slow rolling)		
3" double rubber casters (fast rolling)		
3" double rubber casters with brake (fast rolling)		
2" glides		
3" glides		