PAINT & PAINTING SUPPLIES

IRON GUARD® ACRYLIC ENAMEL INDUSTRIAL COATINGS™



- High gloss, 100% acrylic, waterborne coating for light to moderate industrial use
- Designed for new construction or maintenance use, can be used directly over prepared substrates, including metal
- Chemical and corrosion resistant, fast drying and outstanding early moisture, flash rust and early rust resistance
- Low odour, outstanding adhesion
- VOC: < 100 g/L (0.83 lbs./gal)
- Can be used on steel, iron, aluminum, galvanizing, concrete, masonry, wood and over zinc-rich primers in applications such as tank and cylinders, steel fabricated parts, equipment, machinery, metal buildings, select marine structures, piping, handrails and ornamental iron



NI814

Colour	Model No. 1 Gallon	Price /Each	Model No. 5 Gallon	Price /Each
Gloss White	NI813		KP259	
Gloss Black	NI814		KP260	
Semi-Gloss Black	NI816		-	-
Flat Black	KP262		-	-
Safety Yellow (OSHA)	NI815		-	-
Safety Red (OSHA)	NI818		-	-
Safety Blue (OSHA)	KP263		-	-
Safety Green (OSHA)	KP264		-	-
Light Machinery Gray (ASA-61)	NI822		-	-
Safety Orange (OSHA)	KP266		-	-
Dark Machinery Gray (ASA-49)	KP267		-	-
New Cat Yellow	KP268		-	-

SIERRA METALMAX® DTM ACRYLIC

- This water-based formula contains no VOCs, HAPs or solvent odor and is ideal for schools and settings where paint fumes are an issue
- · Superior resistance to corrosion and humidity; excellent color retention
- · Fast, convenient, single-component system
- · Results in a smooth, washable, professional finish
- Applies direct-to-metal (DTM), including galvanized steel and aluminum; for interior/exterior use
- For use on: Anywhere paint odors or VOC is a concern, food/beverage plants, schools, healthcare, warehouses, metal structures, line equipment
- Size: 1 Gal.

RUST-OLEUM

Surface coverage: 180-545 sq. ft./gal. (4.4-13.4 m²/L)



KP481

Model	Mfg.		Price
No.		Colour	/Each
KP481	210475	Safety Red	
KP482	210477	Safety Yellow	
KP483	238752	White	
KP484	238753	Safety Blue	
KP485	238755	Gray Primer	

5600 ACRYLIC URETHANE FLOOR PAINT

- Convenient, high-gloss, water-based coating is ideal for use in mild industrial or commercial setting
- · Protects concrete floors from dusting, water damage, staining and mildew
- Paint and go no measuring or mixing; minimal surface prep
- Excellent coverage over new and previously coated surfaces; for interior/exterior use
- Dries fast accepts next-day foot traffic; easy brush, spray or roller application
- For use on: Interior/exterior concrete floors, walkways, decks/patios

RUST-OLEUM


- Surface Coverage: 170-270 sq.ft./gal. (4.2-6.6 m²/L)
- Accepted for use in Canadian food processing facilities



KP490

Model Mfg. Container Price No. No. Colour Size /Each KP490 251286 Safety Yellow 1 Gallon KP491 251291 Silver Gray 1 Gallon KP492 251293 Silver Gray 5 Gallons

RUST TOUGH® 250 ACRYLIC ALKYD ENAMEL



- Rust inhibitive, corrosion resistant alkyd enamel can be applied directly to metal
- Protects against mild chemicals, fumes, oil and grease stains and atmospheric corrosion
- Excellent hide, colour & gloss retention, and superior chip, crack and peel resistance
- Low VOC, CARB compliant < 250 g/L
- Can be used on previously painted surfaces, iron, steel, aluminum, galvanized metal or wood
- Acceptable for use in Canadian food processing facilities
- Size: 1 gallon



INDUSTRIAL

AD349

Model		Price
	Colour	/Each
AD350	Safety Yellow	
AD358	Safety Orange	
AD359	Safety Blue	
AD355	Safety Red	
AD345	Gloss White	
AD349	Black	
AD352	Dark Machinery Gray	
AD353	Light Machinery Gray	
AD356	Equipment Yellow	
PRIMER		
AD347	Grey Primer	
AD357	Red Oxide Primer	

EPOXY FLOOR COATING

- Low VOC, low HAP, two component suitable for use on both floors and vertical surfaces
- Can be used on steel, non-ferrous, concrete, masonry, and previously coated surfaces
- Low odour coating ideal for use in schools, healthcare facilities, food service areas, office buildings, hotels or in any area where odors are an issue
- · Resistant to most chemicals and abrasion
- Easy-to-use, two-component system order base and activator separately
- Container Type: Gallon
- · Container Size: 1 gal.
- · Net Volume: 1 gal.
- Finish: Gloss

RUST-OLEUM SIERRA Ferry Maidreance Coding Was to Authoritism for Jam to Authoritism Significant fo

RUST-OLEUM

Model	Mfg.		Price
No.	No.	Colour	/Each
KP899	248280	Osha Yellow	
KP901	208072	Gloss Grey	
KP873	248284	Activator	

5500 ACRYLIC DUSTPROOFER FLOOR SEALER

- Water-based coating seals concrete and prevents dusting in mild industrial or commercial settings
- Seals bare concrete or provides a protective top coat; makes maintenance easy; low-gloss finish
- Excellent coverage over new and previously coated surfaces; for interior/exterior use
- For use on: Floor coating for warehouses, walkways, over strained and painted concrete, retail/commercial
- Size: 1 Gal.
 Surface Coverage: Rough (Broom Finish) First Coat 150 sq. ft./gal., Second Coat- 250 sq. ft./gal. Smooth
 (Float Finish) First Coat- 200 sq. ft./gal., Second Coat
- (Float Finish) First Coat- 200 sq. ft./gal., Second Coat 300 sq. ft./gal. Very Smooth (Trowel Finish) First Coat 300 sq. ft./gal, Second Coat 400 sq. ft./gal.

 Accepted for use in Canadian
- Accepted for use in Canadian food processing facilities

Model No. KP493 Mfg. No. 251282 Price/Each \$



