

WATER PUMPS

GENERAL PURPOSE PUMPS

- For agriculture, irrigation and water transfer over a long distance
- Ideal for general water pumping applications on the farm, home, garden or for light commercial applications TAW070, TAW071 and TAW072 are capable of handling solids up to 1/4", have an Oil Alert™ feature shuts down engine if oil drops below a safe operating level, have a cast aluminum pump housing, impeller and volute and have a mechanical (silicon carbide) seal







Model No.	TAW082 1" Water Pump	TAW070 2" Water Pump	TAW071 3" Water Pump	TAW072 4" Water Pump
Engine:	4-Stroke Honda GX25, 1 HP	4-Stroke Honda GX120, 4 HP	Honda GX160 OHV, 5.5 HP	Honda GX240 OHV, 8.0 HP
Port Size:	1" x 1" (25 mm x 25 mm)	2" x 2" (50 mm x 50 mm)	3" x 3" (75 mm x 75 mm)	4" x 4" (100 mm x 100 mm)
Maximum Capacity:	117 litres/min - 31 GPM	518 litres/min - 137 GPM	1100 litres/min - 290 GPM	1800 litres/min - 476 GPM
Suction Lift:	26'	26'	26'	26'
Maximum Head:	114' (34.75 metres)	137' (41.76 metres)	106' (32 metres)	93' (28.35 metres)
Dimensions:	12.4" L x 8.86" W x 13.4" H	12.4" L x 8.86" W x 13.4" H	21.6" L x 15.4" W x 17.5" H	25.6" x 18.3" W x 24.2" H
Weight:	10 lbs.	10 lbs.	66 lbs.	110 lbs.
Price/Each:	\$	\$	\$	\$

TRASH PUMPS

GENERAL PURPOSE PUMPS

- High output trash pumps, capable of handling solids up to 1" diameter
- Removable front cover for easy cleaning and maintenance
- Oil Alert™ feature shuts down engine if oil drops below a safe operating level
- Cast aluminum pump housing
- Cast iron impeller and volute
- Silicon carbide mechanical seal





Model No.	TAW073 2" Water Pump	TAW074 3" Water Pump	
ngine:	Honda GX160 OHV, 5.5 HP	Honda GX240 OHV, 8.0 HP	
Port Size:	2" x 2" (50 mm x 50 mm)	3" x 3" (75 mm x 75 mm)	
Maximum Capacity:	600 litres/min - 158 GPM	1300 litres/min - 343 GPM	
Suction Lift:	26' (8.0 metres)	26' (8.0 metres)	
Naximum Head:	85' (25.9 metres)	92' (28 metres)	
Dimensions:	25" L x 17" W x 19.5" H	29.5" L x 20.8" W x 25.7" H	
Weight:	99 lbs.	132 lbs.	
Price/Each:	\$	\$	

