

# AIR TOOLS



## 5" PNEUMATIC ANGLE GRINDERS

- Polyurethane grip reduces operator fatigue and vibration
- 5/8" x 11 UNC spindle
- Powerful twin – chamber motor-delivers much higher torque
- Side handle and wrenches included

Model No. THZ674



**aurora tools**

Model No.	Grinding Wheel in mm	Spindle Thread in mm	Free Speed RPM	Average Air Consumption CFM	Air Inlet	Hose Size in mm	Vibration Less Than m/s <sup>2</sup>	Sound Pressure Level dB(A)	Net Weight lbs. kg	Price /Each
THZ674	5 127	5.8 15.9	10000	5	1/4" - 18 NPT	3/8 9.5	3.1	83	3.1 1.41	

## ANGLE GRINDERS

For cleaning, deburring, blending and smoothing

- 0.8 HP motor
- Aluminum alloy housing
- Spiral bevel gearing in angle head
- 1/4" (NPTF) air inlet
- 3/8" minimum hose size

Model No. TG080

Model No. TG081



## 7" ANGLE GRINDERS

For cleaning, deburring, blending, and smoothing

- Use with 7", Type 27 grinding wheels
- 1.12 HP motor
- Aluminum alloy housing
- Spiral bevel gearing in angle head
- 3/8" (NPTF) air inlet
- 3/8" minimum hose size

Model No. TKZ804



**Chicago Pneumatic**

Model No.	Mfg No.	Wheel Size in. (mm)	Spindle Thread"	Free Speed RPM	CFM	dB(A)	Vibration m/s <sup>2</sup>	Overall Length Less Guard in. (mm)	Net Weight Less Guard lbs. (kg)	Price /Each
TG080	CP9120CR	4 (102)	3/8-24	14000	21	84	7.5	9 (229)	4.0 (1.8)	
TG081	CP9121CR	5 (127)	3/8-24	12000	21	84	8.1	9 (229)	4.2 (1.9)	
TKZ804	CP9123	7 (178)	5/8-11	7500	33	93	4.2	13 1/8 (333)	6 1/4 (2.84)	

Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1.

## INDUSTRIAL ANGLE GRINDERS

- Powerful production tool
- Easy maintenance
- Lubricate only every 1000 hours
- Unequaled power to weight ratio



TCW014



TBW661

**Chicago Pneumatic**

Model No.	Mfg. No.	Free Speed RPM	Wheel Max. Capacity mm		Threaded Spindle	Power HP W		Weight lbs. kg		Air Consumption				Air Inlet Thread"	Hose I.D."	Price /Each
										At Free Speed CFM	At Free Speed L/s	At Max Output CFM	At Max Output L/s			
TCW014	CP3450-12AC4	12000	4	100	3/8"-24	1.1	810	3.7	1.7	18	10	36	18	3/8	1/2	
TBW661	CP3450-12AB5	12000	5	127	5/8"-11	1.1	810	6.3	2.9	18	14	36	18	1/2	1/2	