

LIFTING EQUIPMENT

LODESTAR ELECTRIC CHAIN HOISTS

- Features quiet operation, an environment friendly design, easy access to components, high duty cycles, along with less maintenance and enhanced safety features
- Lifetime grease-lubricated gear box
- 5-pocket liftwheel • Zinc-plated chain
- Clutch is located outside the load path, preventing slipping of the load in an overload condition when the brake is not powered
- Fabric chain container and rigid hook suspension standard on every Lodestar
- Hook mount standard, lug mount available upon request
- Standard lift: 10' • Lifetime warranty
- CSA approved and meets ASME B30.16 • Precision gears
- AC electrical brake or double DC brake available
- Variable speed drive (VFD) or traditional 2 speeds available

Model No.	Lift Speed FPM	Voltage	Phase	Capacity lbs.	Weight lbs.	Price /Each
LT615	16	115	1	500	53	
LT616	32	115	1	500	61	
LT617	8	115	1	1000	71	
LT618	16	115	1	1000	61	
LT619	8	115	1	2000	72	
LT620	16	115	1	2000	113	
LT621	8	115	1	4000	131	
LT624	16	575	3	500	61	
LT625	32	575	3	500	64	
LT626	8	575	3	1000	69	
LT627	16	575	3	1000	65	
LT628	16	575	3	2000	110	
LT630	8	575	3	4000	130	

Note: Additional lifts & capacities available on request



HEAVY DUTY GOLD SERIES LEVER CHAIN HOIST

- Chain Grade: Grade 80 • Sealed bearings
- Cast latches • Chain Material: Alloy Steel
- Automatic brake engagement holding load at any height
- Light weight robust construction
- **Caution: Never exceed work load limit**

Model No.	Lift'	Capacity lbs. (tons)	Price /Each
LU617	5	500 (0.25)	
LU619	5	1000 (0.5)	
LU620	5	1500 (0.75)	
LU622	5	3000 (1.5)	
LU624	5	6000 (3)	
LU618	10	500 (0.25)	
LU625	10	6000 (3)	
LU626	10	12 000 (6)	

ELECTRIC CHAIN HOIST

- Multi-disc magnetic brake for positive load holding and spotting
- Adjustable upper and lower limit switches
- Overload limiting clutch and latch-type ridged top hook
- 24-volt pushbutton station fits easily in your hand to allow thumb, trigger or two-handed operation
- Made in the USA
- **5 year warranty**
- Max Lift Speed (ft./min): 16 FPM
- Min Lift Speed (ft./min): 16 FPM
- Voltage: 115V/230V
- Chain Material: Steel
- Phase: 1

Model No.	Mfg No.	Lift'	Capacity	Price /Each
TEA071	9560	10	1000 lbs. (0.5 tons)	
TEA072	9561	15	1000 lbs. (0.5 tons)	
TEA073	9562	20	1000 lbs. (0.5 tons)	
TEA074	9565	10	2000 lbs. (1 tons)	
TEA075	9566	10	2000 lbs. (1 tons)	
TEA076	9567	15	2000 lbs. (1 tons)	
TEA077	9568	20	2000 lbs. (1 tons)	
TEA078	9570	10	4000 lbs. (2 tons)	
TEA080	9572	15	4000 lbs. (2 tons)	
TEA081	9573	20	4000 lbs. (2 tons)	



LEVER HOISTS

SERIES 602 & 603 MINI RATCHET

The Series 602 mini hoist is the most compact ratchet lever hoist in the market

- Use in confined conditions with one hand operation
- Free chaining feature serves to quickly attach the load
- Impact resistant all-steel frame, gear case and cover

Model No.	Lift'	Capacity lbs.	Weight lbs.	Price /Each
LS706	5	550	6	
LS707	5	1100	7	
LS791	10	550	7	
LS792	10	1100	8	

Note: Additional lifts and capacities available on request

SERIES 640 PULLER

The Series 640 long handle puller is ideal for a broad range of pulling applications

- Easy one-hand operation
- Free chaining for fast, easy attachment to load
- Tough yet lightweight aluminum construction and powder coat finish
- **Lifetime warranty**

Model No.	Lift'	Capacity lbs.	Weight lbs.	Price /Each
LS724	5	1500	17	
LS725	5	3000	26	
LS726	5	6000	38	
LS727	5	12000	73	



LS706



LS724

HURRICANE 360° CHAIN HOISTS

- Features a patented chain guide that rotates a full 360° for operation in any direction
- Ideal for drifting applications and use in tight spaces
- Operator can safely stand away from the load at any angle, including from above the unit
- Standard overload limiter • Meets ASME B30.16

Model No.	Lift'	Capacity lbs.	Weight lbs.	Price /Each
LT634	10	1000	18.5	
LT636	10	2000	26.5	
LT638	10	4000	42.1	
LT640	10	6000	68	
LT635	15	1000	23	
LT637	15	2000	28.7	
LT639	15	4000	47.8	
LT641	15	6000	79	

Note: Additional lifts & capacities available on request



MANUAL CHAIN HOISTS

- Simple, efficient, economical design
- Equipped with hardened load chain for flexibility and long wear
- Compact design, low headroom and lightweight steel construction for easy installation, even in confined spaces
- Brake requires no lubrication
- Forged swivel hooks with latches reduce twisting of chain and unintentional unhooking of load when chain is slack
- Standard hand chain drop is 2' less than lift

Model No.	Lift'	Cap. Tons	Wt. lbs.	Price /Each
QG621	10	1/2	18	
Q1069	10	2	61	
LS935	10	3	89	
LS937	10	5	91	
LS930	20	1/2	30	
LS932	20	1	38	
LS934	20	2	80	
LS936	20	3	109	
LS938	20	5	123	

Note: Additional lifts & capacities available on request

