

IRON GUARD® ACRYLIC ENAMEL INDUSTRIAL COATINGS™

- High gloss, 100% acrylic, waterborne coating for light to moderate industrial use
- Designed for new construction or maintenance use, can be used directly over prepared substrates, including metal
- Chemical and corrosion resistant, fast drying and outstanding early moisture, flash rust and early rust resistance
- Low odour, outstanding adhesion
- VOC: < 100 g/L (0.83 lbs./gal)
- Can be used on steel, iron, aluminum, galvanizing, concrete, masonry, wood and over zinc-rich primers in applications such as tank and cylinders, steel fabricated parts, equipment, machinery, metal buildings, select marine structures, piping, handrails and ornamental iron



NI814

Colour	Model No. 1 Gallon	Price/Each	Model No. 5 Gallon	Price/Each
Gloss White	NI813	-	KP259	-
Gloss Black	NI814	-	KP260	-
Semi-Gloss Black	NI816	-	-	-
Flat Black	KP262	-	-	-
Safety Yellow (OSHA)	NI815	-	-	-
Safety Red (OSHA)	NI818	-	-	-
Safety Blue (OSHA)	KP263	-	-	-
Safety Green (OSHA)	KP264	-	-	-
Light Machinery Grey (ASA-61)	NI822	-	-	-
Safety Orange (OSHA)	KP266	-	-	-
Dark Machinery Grey (ASA-49)	KP267	-	-	-
New Cat Yellow	KP268	-	-	-

SIERRA METALMAX® DTM ACRYLIC

- This water-based formula contains no VOCs, HAPs or solvent odor and is ideal for schools and settings where paint fumes are an issue
- Superior resistance to corrosion and humidity; excellent color retention
- Fast, convenient, single-component system
- Results in a smooth, washable, professional finish
- Applies direct-to-metal (DTM), including galvanized steel and aluminum; for interior/exterior use
- For use on: Anywhere paint odors or VOC is a concern, food/beverage plants, schools, healthcare, warehouses, metal structures, line equipment
- Size: 1 Gal.
- Surface coverage: 180-545 sq. ft./gal. (4.4-13.4 m²/L)



KP481

■ ■ ■ RUST-OLEUM

Model No.	Mfg. No.	Colour	Price /Each
KP481	210475	Safety Red	-
KP482	210477	Safety Yellow	-
KP483	238752	White	-
KP484	238753	Safety Blue	-

5600 ACRYLIC URETHANE FLOOR PAINT

- Convenient, high-gloss, water-based coating is ideal for use in mild industrial or commercial setting
- Protects concrete floors from dusting, water damage, staining and mildew
- Paint and go — no measuring or mixing; minimal surface prep
- Excellent coverage over new and previously coated surfaces; for interior/exterior use
- Dries fast — accepts next-day foot traffic; easy brush, spray or roller application
- For use on: Interior/exterior concrete floors, walkways, decks/patios
- Surface Coverage: 170-270 sq.ft./gal. (4.2-6.6 m²/L)
- Accepted for use in Canadian food processing facilities



KP490

■ ■ ■ RUST-OLEUM

Model No.	Mfg. No.	Colour	Container Size	Price /Each
KP490	251286	Safety Yellow	1 Gallon	-
KP491	251291	Silver Grey	1 Gallon	-
KP492	251293	Silver Grey	5 Gallons	-

RUST TOUGH® 250 ACRYLIC ALKYD ENAMEL

- For interior/exterior industrial, institutional, commercial and maintenance use in moderate to severe environments
- Rust inhibitive, corrosion resistant alkyd enamel can be applied directly to metal
- Protects against mild chemicals, fumes, oil and grease stains and atmospheric corrosion
- Excellent hide, colour & gloss retention, and superior chip, crack and peel resistance
- Low VOC, CARB compliant < 250 g/L
- Can be used on previously painted surfaces, iron, steel, aluminum, galvanized metal or wood
- Acceptable for use in Canadian food processing facilities
- Size: 1 gallon



AD349

Model No.	Colour	Price /Each
AD350	Safety Yellow	-
AD358	Safety Orange	-
AD359	Safety Blue	-
AD355	Safety Red	-
AD345	Gloss White	-
AD349	Black	-
AD352	Dark Machinery Grey	-
AD353	Light Machinery Grey	-
AD356	Equipment Yellow	-
PRIMER		
AD347	Grey Primer	-
AD357	Red Oxide Primer	-

EPOXY FLOOR COATING

- Low VOC, low HAP, two component suitable for use on both floors and vertical surfaces
- Can be used on steel, non-ferrous, concrete, masonry, and previously coated surfaces
- Low odour coating ideal for use in schools, healthcare facilities, food service areas, office buildings, hotels or in any area where odors are an issue
- Resistant to most chemicals and abrasion
- Easy-to-use, two-component system—order base and activator separately
- Container Type: Gallon
- Container Size: 1 gal.
- Net Volume: 1 gal.
- Finish: Gloss



■ ■ ■ RUST-OLEUM

Model No.	Mfg. No.	Colour	Price /Each
KP899	248280	Osha Yellow	-
KP901	208072	Gloss Grey	-
KP873	248284	Activator	-

5500 ACRYLIC DUSTPROOFER FLOOR SEALER

- Water-based coating seals concrete and prevents dusting in mild industrial or commercial settings
- Seals bare concrete or provides a protective top coat; makes maintenance easy; low-gloss finish
- Excellent coverage over new and previously coated surfaces; for interior/exterior use
- For use on: Floor coating for warehouses, walkways, over strained and painted concrete, retail/commercial
- Size: 1 Gal.
- Accepted for use in Canadian food processing facilities
- Surface Coverage: Rough (Broom Finish) - First Coat - 150 sq. ft./gal., Second Coat- 250 sq. ft./gal. Smooth (Float Finish) - First Coat- 200 sq. ft./gal., Second Coat - 300 sq. ft./gal. Very Smooth (Trowel Finish) - First Coat - 300 sq. ft./gal., Second Coat - 400 sq. ft./gal.



Model No. KP493
Mfg. No. 251282
Price/Each \$

■ ■ ■ RUST-OLEUM