

D-HANDLE JIG SAW

- The M18 Fuel D-Handle Jig Saw combines power, blade speed and precision, to deliver quality cuts in a wide variety of materials and applications
- Features a variable-speed two-finger trigger
- Toolless blade-change and bevel adjust
- Integrated LED light with on/off blower to Maximize cutline visibility
- Includes: (1) M18 FUEL™ D-Handle Jig Saw, (1) Anti-Splinter Guard, (1) Dust Collection Tube, (1) Dust Cover, (1) General Purpose Jigsaw Blade, (1) Hex Wrench, (1) Shoe Guard

SPECIFICATIONS

Voltage:	18 V
Battery Type:	Lithium-Ion
Strokes per Minute (SPM):	3500
Stroke Length:	1"



Model No.	Mfg. No.	Desc.	Price/Each
UAD742	2737-20	Tool Only	

MAX JIG SAW KIT

- All-metal, lever-action, keyless blade change allows for quick and easy blade changes
- All-metal, keyless shoe bevel with detents at 0°, 15°, 30°, and 45° provides versatility for easy bevel cutting
- 4-position orbital action provides control of cut quality and speed
- Adjustable dust blower keeps line of cut clear of chips
- Variable speed for versatility in a multitude of materials and applications
- Anti-slip comfort grip for increased comfort and control
- Accepts T-shank jig saw blades for optimal holding power and professional results
- Includes: 20 V Max jig saw, 20 V Max XR* Premium lithium-ion 4.0 Ah battery, Charger, Blade, Kit box



SPECIFICATIONS

Voltage:	20 V
Battery Type:	Lithium-Ion
Strokes per Minute (SPM):	0-3000
Stroke Length:	1"
Tool Weight:	6.8 lbs.

Model No.	Mfg. No.	Desc.	Price/Each
TLV838	DCS331B	Tool Only	
TLV839	DCS331M1	Tool & Kit	

MAX XR® CORDLESS JIG SAW

- Brushless motor delivers efficient performance for longer runtime
- Compact size for easy grip and maximum control
- Bright LED light helps to illuminate dimly lit work surfaces
- Variable speed trigger and dial provide precise speed control
- All-metal, lever-action keyless blade change allows for quick and easy t-shank blade changes
- Integrated dust blower helps clear line of sight while cutting
- 4-position orbital action provides control of cut quality and speed
- All-metal, keyless shoe bevel with detents at 0°, 15°, 30°, and a positive stop at 45° for easy adjustment
- No-mar shoe cover to help protect work surface from scratches
- Accepts t-shank jig saw blades for optimal holding power and professional results
- Includes: Jig saw, Jig saw blade



SPECIFICATIONS

Voltage:	20 V
Battery Type:	Lithium-Ion
Strokes per Minute (SPM):	0-3200
Stroke Length:	1"

Model No.	Mfg. No.	Desc.	Price/Each
UAK905	DCS334B	Tool Only	

CORDLESS 1" STEEL ROD CUTTER

- Ideal for cutting threaded rod and rebar
- Carbide tooth blade limits burring of threaded rod for fast and easy installation of nuts
- Automatic torque Drive Technology (ADT) feature adjusts the torque and speed according to the load condition, enabling rapid movement between high speed and high torque applications
- Brushless DC motor with high power to weight and size ratio
- Brushless DC motor generates less heat buildup and is ideal for prolonged use in manufacturing / production applications
- Battery protection system provides over-discharge, temperature and circuit protection for enhanced performance, battery cycle life and overall battery life
- Electric brake stops blade 3-5 seconds after trigger is released for increased operator safety
- LED charge level indicator displays approximate remaining battery power
- Ergonomic soft rubber grip design for vibration absorption and comfortable operation features re-contoured rear grip portion and ribbed grip for improved hold



Model No.	Mfg. No.	Desc.	Price/Each
UAV671	DSC2512K	Tool Only	

M18™ COMPACT HEAT GUN

- High performance heating coil reaches operational temperature in 7 seconds (30% faster heat up than corded)
- Guarded nozzle provides increased protection for work surfaces
- Ladder hook allows users to easily hang the tool between applications
- Most compact electric heat gun at 6.4" long
- Compatible with all M18 Redlithium™ battery packs
- LED Light

SPECIFICATIONS

Voltage:	18 V
Amps:	5 A
Battery Type:	Lithium-Ion
Temperature:	875°F(468° C)
Temperature Setting:	Variable

Model No.	Mfg. No.	Desc.	Price/Each
TY032	2688-20	Tool Only	

