



MIG GUNS

- Recommended for applications using solid and flux core wire
- Guns are complete with 15' cable length
- A complete selection of replacement parts for most brands of guns is available
- Contact us for pricing on guns with different amperage ratings or cable lengths



BERNARD® STYLE REPLACEMENT AIR-COOLED MIG GUNS

200 AMPS

Rating:

- 200 Amps CO₂ @ 100% duty cycle
- 150 Amps mixed gas @ 100% duty cycle
- Wire Capacity: 0.023" - 0.045"

300 AMPS

Rating:

- 300 Amps CO₂ @ 100% duty cycle
- 250 Amps mixed gas @ 100% duty cycle
- Wire Capacity: 0.030" - 0.062"

350 AMPS

Rating:

- 350 Amps CO₂ @ 100% duty cycle
- 250 Amps mixed gas @ 100% duty cycle
- Wire Capacity: 0.030" - 0.062"

400 AMPS

Rating:

- 400 Amps CO₂ @ 100% duty cycle
- 300 Amps mixed gas @ 100% duty cycle
- Wire Capacity: 0.035" - 5/64"



| Model No. | Mfg. No. | Feeder Plug | Price /Each |
|-----------------|------------|-------------------|-------------|
| 200 AMPS | | | |
| 379-4395 | B2-4215A | Bernard DP | |
| 379-1101 | B2-4215AM | Miller DP | |
| 379-4510 | B2-4215AE | Euro DP | |
| 379-4201 | B2-4215AL | Lincoln DP | |
| TTT009 | B2-4215AWM | Lincoln Wirematic | |
| TTT010 | B2-4215AT | Tweco DP | |
| 300 AMPS | | | |
| NT172 | B2-4315A | Bernard DP | |
| NT174 | B2-4315AM | Miller DP | |
| NT173 | B2-4315AE | Euro DP | |
| NT204 | B2-4315AL | Lincoln DP | |
| TTT011 | B2-4315AWM | Lincoln WM 250 | |
| NT175 | B2-4315AT | Tweco DP | |

| Model No. | Mfg. No. | Feeder Plug | Price /Each |
|-----------------|-------------|-------------------|-------------|
| 350 AMPS | | | |
| 379-4570 | B2-43515A | Bernard DP | |
| 379-1113 | B2-43515AM | Miller DP | |
| TTT012 | B2-43515AE | Euro DP | |
| 379-4223 | B2-43515AL | Lincoln DP | |
| TTT013 | B2-43515AWM | Lincoln Wirematic | |
| 379-4920 | B2-43515AT | Tweco DP | |
| 400 AMPS | | | |
| TW978 | B2-4415A | Bernard DP | |
| TW983 | B2-4415AM | Miller DP | |
| TW979 | B2-4415AE | Euro DP | |
| TW981 | B2-4415AL | Lincoln DP | |
| TW984 | B2-4415AT | Tweco DP | |



Contact Tip



Long Contact Tip



BERNARD® STYLE CONSUMABLES

| Model No. | Mfg. No. | Description | Size" | 200 Amps | 300 Amps | 350 Amps | 400 Amps | Price /Each |
|-----------|----------|----------------------|-------|----------|----------|----------|----------|-------------|
| NT183 | B7497 | Contact Tip | 0.023 | X | X | X | | |
| NT179 | B7488 | Contact Tip | 0.030 | X | X | X | | |
| NT180 | B7489 | Contact Tip | 0.035 | X | X | X | X | |
| PB052 | B7496 | Contact Tip | 0.040 | X | X | X | X | |
| NT181 | B7490 | Contact Tip | 0.045 | X | X | X | X | |
| PB054 | B7498 | Contact Tip | 0.052 | X | X | X | X | |
| NT182 | B7491 | Contact Tip | 1/16 | X | X | X | X | |
| PB048 | B7492 | Contact Tip | 5/64 | | | | X | |
| PB050 | B7494 | Contact Tip | 7/64 | | | | X | |
| TW993 | B1589 | Contact Tip, Long | 0.035 | X | X | X | X | |
| TW994 | B1590 | Contact Tip, Long | 0.045 | X | X | X | X | |
| PB044 | B1598 | Contact Tip, Long | 0.052 | X | X | X | X | |
| TW995 | B1591 | Contact Tip, Long | 1/16 | X | X | X | X | |
| TW996 | B1592 | Contact Tip, Long | 5/64 | | | | X | |
| TW997 | B1593 | Contact Tip, Long | 3/32 | | | | X | |
| 379-1124 | B4281 | Contact Tip, Tapered | 0.035 | X | X | X | | |
| TTT133 | B4282 | Contact Tip, Tapered | 0.045 | X | X | X | | |
| TTT134 | B4283 | Contact Tip, Tapered | 0.052 | X | X | X | | |
| TTT132 | B4280 | Contact Tip, Tapered | 1/16 | X | X | X | | |

Note: All reference to genuine manufacturer's equipment numbers and/or trade names or trademarks are for identification and convenience only. The trademarks and trade names are the property of their respective owners.

Continued on next page