

BOOSTER CABLES

- Clamp design fits on both top-post and side-post batteries
- Surge suppressor on 2, 4, and 6 gauge cables protect a vehicles computer system from power surges during boosting
- Cable remains flexible in temperatures as low as -40°C
- Tangle-free



XE495



XE494

AURORA
TOOLS

Model No.	Wire Gauge	Amps	Length'	Price /Each
XE494	8	150	10	
XE495	6	400	16	
XE496	4	400	20	
XE497	2	400	20	

SYNTRAX LIMITED SLIP 75W-90 GEAR OIL

- Premium synthetic formulation for added assurance during extended drain intervals
- Improved thermal stability and excellent shear stability for superior wear protection
- Full compatibility with all conventional and synthetic API GL-5 and MT-1 gear oils
- Specific Gravity at 15.6°C: 0.868
- Viscosity Index: 135
- Density, lb/gal: 7.23



Model No.	Mfg. No.	Size	Price /Each
FLU293	201666	946 ml	

LOCK DE-ICER

- Rapidly thaws frozen locks
- Lubricates & reduces wear
- For auto & home use



Model No.	Mfg. No.	Size	Price /Each
MP723	35-276WP	30 ml	

TRANSYND 668 FULL-SYNTHETIC AUTOMATIC TRANSMISSION FLUID

- Castrol TranSynd 668 is a premium, full-synthetic automatic transmission fluid specifically formulated for Allison Transmission® on-highway automatic transmissions
- TranSynd 668 provides oxidative stability, anti-wear performance, and friction durability, as well as TES 668™ specification differentiators such as extended anti-shudder durability and extended clutch friction durability
- This fluid features an Allison TES 668 approval
- The TES 668 spec is fully backwards compatible for TES 295® applications, but is not backwards compatible for TES 468™ applications
- Colour: Red



Model No.	Mfg. No.	Size	Price /Each
AH177	908916	3.78 L Bottle	
AH178	908959	18.93 L Pail	
AH179	908906	208.2 L Drum	

SAE 30 NON-DETERGENT MOTOR OIL

- Suitable for use in compressors and other stationary pumps
- May also be used as a hydraulic fluid on small volume, low pressure systems



Wakefield

Model No.	Mfg. No.	Size	Price /Each
AH198	4402842	1 L	

GASKET KLEEN™

- Plastic Safe: No
- Flashpoint: 13°C
- Fast evaporation rate
- Used for the removal of conventional and formed in place gaskets on motors, pumps and flanges



Model No.	Mfg. No.	Size	Price /Each
MLP071	75021	340 g	

Control spills
with confidence

ZENITH[®]
Safety Products

